




## C(D)Q2W, Compact Cylinder, Double Acting Double Rod w/Auto Switch Mounting Groove CDQ2WB40TF-15DZ

Datasheet

### General series information


- Double acting, double rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

### Standard specifications

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Low Speed                        | None                                      |
| Stroke                           | 15 mm                                     |
| Magnet                           | D (Built-in)                              |
| Rod End Options                  | None                                      |
| Made of Stainless Steel          | None                                      |
| Lead Wire or Pre-wired Connector | 0.5 m (Or None in the Case of No Switch)  |
| Auto Switch                      | No Switch                                 |
| Mounting                         | B (Through Hole [Standard])               |
| Bore Size                        | Ø40 mm                                    |
| Type                             | Standard                                  |
| Fluororubber Seal                | None                                      |
| Number                           | 2 pcs. (Or None in the Case of No Switch) |
| Auto Switch Groove               | Z (Auto Switch Mounting Grooves)          |
| Port Thread                      | TF                                        |
| Temperature Resistance           | None                                      |
| Body Option                      | Standard (Rod End Female Thread)          |
| Pressure medium                  | Compressed air                            |
| Number of pneumatic connections  | 2 pcs.                                    |

|                            |               |
|----------------------------|---------------|
| Mode of operation of drive | Double acting |
| Weight                     | 0.413 Kg      |

Dimensions



## Additional information

Catalogue

[CQ2-Z-D\\_EU.pdf](#)

Operation manuals

[OM\\_CQ2x\\_OM0002MEN.pdf](#)