




JC(D)Q, Compact Cylinder, Double Acting Single Rod JCQA20-10

Datasheet

General series information

- Double acting, single rod, compact cylinder.
- Lightweight 25 g (ø12 stroke 5).
- Bore sizes (mm): 12 ~ 100.
- Strokes up to 50 mm.
- Bumper cushion.
- Auto switches can be mounted on 4 surfaces.



Double-acting, single-rod cylinder


Standard specifications


Mounting	A (Both Ends Tapped)
Bore Size	20 mm
Stroke	10 mm
Number	2 pcs. (Or None in Case of No Switch)
Magnet	None
Port Thread	M thread: Ø12 to Ø40, Rc: Ø50 to Ø100
Lead Wire or Pre-wired Connector	0.5 m (Or None in the Case of No Switch)
Auto Switch	No Switch
Pressure medium	Air
Maximum temperature of pressure medium	60 °C
Minimum temperature of pressure medium	5 °C
Maximum operating pressure	0.7 MPa
Minimum operating pressure	0.05 MPa
Proof pressure	1.0 MPa
Maximum ambient temperature	60 °C
Minimum ambient temperature	5 °C
Number of pneumatic connections	2 pcs.

Pneumatic input connection	M5 x 0.8
Theoretical cylinder force, advance stroke (at 0.5 MPa)	157 N
Theoretical cylinder force, return stroke (at 0.5 MPa)	132 N
Maximum piston speed	500 mm/s
Type of cushioning	Rubber bumper
Piston rod end	Female thread
Geometric form of the piston rod	Single rod
Minimum piston speed	50 mm/s
Lubrication	Not required (Non-lube)
Weight	0.047 Kg

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

Dimensions





Additional information
Catalogue

JCQ-D_EU.pdf