





JSX, Direct Operated 2-Port Solenoid Valve

JSX11-SF201F-5WN

Datasheet

General series information

- Applicable fluid: air, water, oil
- Flow rate up to 25 l/min (water)
- Orifice diameter: 1.6 to 7.1 mm
- Port size: 1/8" to 3/8"
- Body material: stainless steel, brass and aluminium
- Coil material: stainless steel
- Enclosure: IP67.




Directional control valve 2/2-way valve, closed normal position Controlled by solenoid coil with one winding, direction of actuation towards the valving element Return with mechanical control spring

Standard specifications


Size	1 (Series 10)
Body Material	S (Stainless Steel)
Seal Material	F (FKM)
Orifice Diameter/Port Size	201 (Orifice Diameter: ø2.4 mm; Port Size: 1/8)
Thread Type	F (G)
Rated voltage	5 (24 VDC)
Electrical Entry	WN (M12 Connector/without Connector Cable with Surge Voltage Suppressor)
Oil-free Option	None
Bracket	None
Maximum temperature of pressure medium	60 °C
Minimum temperature of pressure medium	Air: -10 °C, Water: 1 °C, Oil: -5 °C
Maximum operating pressure	1 MPa
Proof pressure	2.0 MPa
Maximum ambient temperature	60 °C
Minimum ambient temperature	-20 °C

Conform to the European RoHS Directive	Conform
Enclosure	IP67 (IP65 for the DIN terminal)
Allowable voltage fluctuation	±10% of rated voltage
Allowable leakage voltage	2 % or less of the rated voltage
Power consumption	4 W
Temperature rise	65 °C
External Leakage	Air: 1 cm³/min, Water and Oil: 0.1 cm³/min
Weight	0.175 Kg

Dimensions



Constructions



Component Parts

No.	Description	Material	
1	Clip	Stainless steel	
2	Solenoid coil	Stainless steel, Cu,	
3	Stopper	PPS	
4	Tube assembly	Stainless steel	
5	Armature assembly	Stainless steel, PPS, NBR (FKM, EPDM)	
6	Spring	Stainless steel	
7	Set nut	Stainless steel	
8	Gasket	NBR, (FKM, EPDM)	
9	Body	Stainless	Brass

Additional information

Catalogue	JSX-Da_EU.pdf
Declaration of conformity	newDoC_JSX_TF1Z310EN.pdf
Installation manuals	IM_JSX_TF2Y014EN-C.pdf