Belt Drive, Motorless - LEFB
LEFB40NZS-700

Datasheet

General series information

- Body size: 25, 32, 40
- Stroke: 300 to 3000 mm
- AC servo motor 100, 200, 400 W
- Horizontal workload: up to 25 kg
- Speed: 2000 mm/s
- Acceleration: up to 20000 mm/s²
- Compatible with several motors: OMRON, Siemens AG, Beckhoff automation and more.

Standard specifications

Series	LEFB (Belt Drive)
Size	40
Motor Mounting Position	Top Mounting
Motor Type	NZ (Mounting Type Z)
Lead	S
Stroke	700 mm
Auto Switch Mounting Bracket	None
Positioning Pin Hole	Housing B Bottom
Positioning repeatability	± 0.06 mm
Lost motion	0.1 mm
Impact/Vibration resistance	50/20 m/s2
Horizontal work load	25 kg
Speed	2000 mm/s
Max. Acceleration/deceleration	20000 mm/s2
Operating temperature range	5 - 40 ºC
Weight	7.500 Kg

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com

Dimensions



Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com

Additional information

Catalogue LE_motorless-E_EU.pdf

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com