





MXJ, Miniature High Precision Slide Table (ø4.5, ø6, ø8) MXJ4-5

Datasheet

General series information

- Strokes up to 20 mm.
- Front and top mounting.
- Travelling parallelism: 0.005 mm.
- Clean room specification available.
- Operating pressure range: 0.15 to 0.7 MPa.




*Double-acting cylinder with cushioning
adjustable at both ends, double piston rod*

Standard specifications


Bore Size	4.5 mm
Switch Rail	w/Magnet and Switch Rail
Function	w/o Axial Piping
Stroke	5 mm
Specifications	Standard Type
Number	2 pcs. (Or None in Case of No Switch)
Adjuster	w/o Adjuster
Lead Wire or Pre-wired Connector	0.5 m (Or None in the Case of No Auto Switch)
Auto Switch	No Switch
Symmetric	Standard
Maximum operating pressure	0.7 MPa
F007-MIN_OP_PRESSURE	0.15 MPa
Proof pressure	1.05 MPa
Maximum ambient temperature	60 °C
Minimum ambient temperature	-10 °C
Conform to the European RoHS Directive	Conform
Maximum piston speed	500 mm/s
Minimum piston speed	50 mm/s

Port size	M3
Lubrication	Non-Lube
Circulating fluid	Air
Stroke length tolerance	+ 1~0 mm
Action	Double Acting
Weight	0.065 Kg

Dimensions



Constructions



Component Parts

No.	Description	Material	Note
1	Body	Martensitic stainless steel	Heat treated
2	Table	Martensitic stainless steel	Heat treated
3	Rod	Stainless steel	
4	Piston	Brass	Electroless nickel plated
5	Rod cover	Resin	
6	Head cap	Resin	
7	Floating bushing A	Stainless steel	
8	Floating bushing B	Stainless steel	
9	Roller stopper A	Stainless steel	
10	Roller stopper B	Stainless steel	
11	Rod bumper	Polyurethane	
12	Plate	Stainless steel	
13	Plug	Steel + Fluorine	Nickel plated
14	Piston seal	NBR	
15	Rod seal	NBR	
16	O-ring	NBR	
17	Steel balls	High carbon chrome bearing steel	

Note) Use caution because the martensitic stainless steel is inferior in corrosiveness when compared with austenitic stainless steel.

Additional information

Catalogue

[MXJ-B_EU.pdf](#)