



PF3W5-Z, Digital Flow Switch for Water, Remote Sensor Unit, IP65

PF3W540-F06-1TN-Z

Datasheet

General series information

- Compact size.
- Built-in temperature sensor.
- IP65.



Flow meter

Standard specifications

Rated Flow Range	40 (5 to 40 l/min)
Flow Adjustment Valve	W/o Flow Adjustment Valve
Thread	F (G)
Port Size	06 (3/4)
Output Specification/Temperature Sensor	1T (Out 1 Flow Rate: Analogue 1 to 5 V; Out 2 Temperature: Analogue 1 to 5 V; Temperature Sensor: w/Temperature Sensor)
Lead Wire	N (w/o Lead Wire and M8 Connector)
Unit Specification	Instantaneous Flow: L/min, Temperature: °C
Bracket	None
Calibration Certificate	None
Proof pressure	1.5 Mpa
General power supply	12 - 24 VDC ±10 %
Response time	0.5 s/1 s/2 s (linked with the switch output)
Current consumption	50 mA or less
Material	PPS, Stainless steel 304, FKM, SCS13, Non-grease
Operating humidity range	Operation, Storage: 35 to 85 % R.H. (No condensation)
Enclosure	IP65
Repeatability	±2 % F.S.
Applicable fluid	Water and ethylene glycol aqueous solution (with viscosity of 3 mPa·s [3 cP] or less)

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.


SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com


Analog current output	4 to 20 mA Max. load impedance: 300 Ω for 12 VDC, 600 Ω for 24 VDC
Analog voltage output	1 to 5 V Output impedance: 1 kΩ
Operating temperature range	0 to 50 °C (No freezing or condensation)
Pressure range	0 - 1 MPa
Accuracy	Display value: ±3 % F.S. Analogue output: ±3 % F.S.
Indicator light	Output 1, Output 2: Orange
Withstand voltage	1000 VAC for 1 minute between terminals and housing
Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing
Temperature characteristics	±5 % F.S. (25 °C standard)
Standards	CE, UL
Flow detection method	Karman vortex
Fluid temperature	0 to 90 °C (No freezing or condensation)
Pressure loss (without flow adjustment valve)	45 kPa or less at the maximum flow
Weight	0.233 Kg


Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.


SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com


Dimensions















Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com

Constructions



Component Parts

No.	Description	Material	Note
1	**Attachment**	Stainless steel 304	PF3W704/720/740/504/520/540
		SCS13	Stainless steel 304 equivalent, PF3W711/511
2	**Seal**	FKM	
3	**Body**	PPS	
4	**Sensor**	PPS	
5	**Temperature sensor**	Stainless steel 304	
6	**Temperature sensor body**	PPS	
7	**Flow adjustment valve body**	PPS	
8	**Flow adjustment valve cover**	PPS	
9	**Flow adjustment valve shaft**	Stainless steel 304	
10	**Shaft support**	PPS	

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com

Additional information

Catalogue	PF3W-Z_L-B_EU.pdf
Declaration of conformity	newdoc_pf_tf1w35en.pdf newDoC_PF3W_TF125-158EN.pdf DoC_PF3Wx_TFG0006.pdf newDoC_PF3W_TF1V119EN-A.pdf
Installation manuals	IM_PF3W5_TF2Z082EN-B.pdf IM_PF3W7-L_TF2Z088EN-A.pdf
Operation manuals	OM_PF3W5_OMN0010EN-L.pdf OM_PF3W7_OMW0010EN-I.pdf

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.

SMC CORPORATION Zuazobidea 14, 01012, Vitoria-Gasteiz, Álava +34 945184100 +34 945184126 www.smc.eu support.marketingeurope@smc.com