

Model		Non plug-in Metal base (Type 40-41)	Plug-in Connector Connecting base (Type 10)																				
			Parallel wiring												Serial wiring								
			D-Sub			Flat ribbon cable						Terminal block box		Lead wire			EX120	EX250	EX260	EX600			
			FC	F	FW	P	PC	PG	PGC	PH	PHC	TC	T	L1	L2	L3	S3	S#	S#	S6			
Manifold style		Non plug-in bar stock type - Rigid manifold (manifold with a fixed number of stations)	Plug-in stacking type base - Modulate assembly (a tie-rod base manifold which allow increasing/decreasing of the number of stations)																				
SUP&EXH port size		Common SUP & EXH (2 EXH port, EA, EB)	Common SUP & EXH (1 EXH port, E)																				
Valve stations	All double wiring	2 to 20	2 to 12			2 to 9		2 to 4		2 to 16		2 to 10		2 to 16		2 to 8		2 to 4		2 up to 8		2 up to 16	
	All single wiring		2 to 24			2 to 18		2 to 8		2 to 24		2 to 20		2 to 24		2 to 16		2 to 8		2 up to 16		2 up to 24	
Valve size mounting		JSY1000 / JSY3000 / JSY5000																					
P, E port size	JSY1000	1/8"	Ø 8 One-touch fitting																				
	JSY3000	1/4"	Ø 10 One-touch fitting																				
	JSY5000	3/8"	Ø 12 One-touch fitting																				
A, B port size (piping type)		Thread piping Straight One-touch fitting (Fixed) Straight One-touch fitting (Replaceable)	Straight One-touch fitting																				
Enclosure	JSY1000	IP40	IP20	IP40	-	IP40	IP20	IP40	IP20	IP40	IP20	IP40			IP20	IP40							
	-		IP67		-		-		-		IP67			IP67									
	JSY5000		-	-	-	-	-	IP67			IP67			IP67									